

LED line

Code: 249921

EAN: 5901583249921

LED line® UFO T-Series 220-240V AC
100W 13000LM 4000K 120°



product_card.label_technical_data

Parameter	Value
Luminous efficacy	130 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	13000 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP65
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	50 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	black
The lumen maintenance factor	96 %
Lamp's diameter	200
Beam angle	120 °
Material (cover)	polycarbonate
Material (housing)	aluminum

Parameter	Value
LED type	SMD3030
LED quantity	144
Lifespan	50000
Power Factor	0,95
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40÷45 °C
For indoor and outdoor use	YES
IEC protection class	I
IK protection rating	08
Full box quantity	1 pc
Lamp's warm-up time to 60%	1
Height	250 mm
Energy class	A+
Power	100 W
Voltage	220-240 V AC
Correlated colour temperature	4000 K

LED line


Code: 249921

EAN: 5901583249921


LED line® UFO T-Series 220-240V AC
100W 13000LM 4000K 120°

product_card.label_dimensions


product_card.label_curve_light



product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	270
Height	215 mm
Length	270 mm
Weight	3,16 kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	1
Width	270 mm
Height of collective packaging	215
Length	270 mm
Weight	3,16 kg
Volume	0,015 m3



Europallet

Number of pieces/tapes in meters euro pallet	56
Quantity collective euro pallet	56
Weight of a euro pallet	176,96 kg
Pallet height	1649
Quantity in 1 layer	8
Number of layers	7

LED line

Code: 249921

EAN: 5901583249921

**LED line® UFO T-Series 220-240V AC
100W 13000LM 4000K 120°**

Example application