

LED line PRIME

Code: 241772-II

EAN: 5905378201859

**LED bulb E27 4000K 13W 1820lm 230V
280° A65 Ceramic PRIME**



LED bulb E27 13W 4000K 1820lm from LED line PRIME is an advanced light source that provides excellent energy efficiency with 13W power and 1820 lumen light stream. It is characterized by a neutral white colour of light with a temperature of 4000 K. Thanks to the lighting angle up to 280°, it effectively dissipates the light in the rooms. Made of durable glass and ceramics, it works with a voltage of 170 to 250 V AC and has a life of up to 30 thousand.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 13 W
Voltage	• 170-250 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	140
Luminous flux	1820 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Lamp's type	A65
Beam angle	280 °
LED type	SMD2835
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	115
Fixture's diameter	65 mm
Colour	White
Material	Ceramic
Material (housing)	Ceramics
Material (cover)	glass

LED line PRIME


Code: 241772-II

EAN: 5905378201859

**LED bulb E27 4000K 13W 1820lm 230V
280° A65 Ceramic PRIME**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	130 mm
Height	185 mm
Length	130 mm
Weight	0,07 kg

Bulk packaging

Quantity	100
Width	360 mm
Height	305 mm
Length	705 mm
Volume	0,077 m3
Weight	8 kg
Comments	

Europallet

Quantity	25000
Height	1830 mm
Quantity in layer	300
Number of layers	6
Bulk quantity	1800
Weight	144 kg

LED line PRIME

Code: 241772-II

EAN: 5905378201859

**LED bulb E27 4000K 13W 1820lm 230V
280° A65 Ceramic PRIME**

Example application