

LED line PRIME

Code: 204317

EAN: 5905378204317

**Linear luminaire FUSION 4000K 60W
7800lm 120*120° IP20 150cm white
PRIME 0-10V**



FUSION linear setting from LED line PRIME is an ideal solution for those looking for effective lighting. With a power of 60 W and a light stream of 7800 lm, it guarantees high light performance of 130 lm/W. Color temperature 4000 K provides natural, white light. The use of 0-10V dimming technology and a wide angle of 120° distribution allows precise adjustment of lighting.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 60 W
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	7800
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	52


LED line PRIME

Code: 204317

EAN: 5905378204317


**Linear luminaire FUSION 4000K 60W
7800lm 120*120° IP20 150cm white
PRIME 0-10V**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Width	1444 mm
Height	52 mm
Length	70 mm
Weight	1,97 kg

Bulk packaging

Quantity	12
Width	1550 mm
Height	260 mm
Length	260 mm
Volume	0,104 m3
Weight	23,89 kg
Comments	

Europallet

Quantity	144
Height	1550 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	286,8 kg

LED line PRIME

Code: 204317

EAN: 5905378204317

**Linear luminaire FUSION 4000K 60W
7800lm 120*120° IP20 150cm white
PRIME 0-10V**

Example application