

LED line PRIME bulb LED E14 9W 6500K 1260lm 170-250V C37 Candle



Manufacturer issues a 5-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Voltage range and voltage type



Lamp type



Lifespan



The structural design of this product ensures effective heat dissipation.



Beam angle



Ambient temperature suitable for operation




LED type

Parameter	Value
Luminous efficacy	140 lm/W
Power	9 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1260 lm
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	30 000
Material	Ceramic
Supply voltage range and voltage type	170-250 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %


Parameter	Value
Lamp's type	C37
Lamp's diameter	37
Beam angle	220 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	111 mm
Master carton weight (kg)	7

Single packaging




Width	68 mm
Height	142 mm
Length	68 mm
Weight	0,06 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	100 szt.
Width	500 mm
Height of collective packaging	270 mm
Length	255 mm
Weight	7 kg
Volume	0,034 m ³

Europallet



Quantity collective euro pallet	4200 szt.
Weight of a euro pallet	294 kg
Pallet height	1890 mm
Quantity in 1 layer	600 szt.
Number of layers	7