


LED line LITE HighBay luminaire STREAKBAY 150W 4000K 15000lm



The **STREAKBAY High Bay LED** is an advanced lighting fixture ideal for industrial applications. With a robust die-cast aluminum construction and an IP65 protection rating, STREAKBAY is highly suited for harsh environments, ensuring reliable performance even in extreme temperatures.

This fixture offers a wide range of models with power options of 50W, 100W, 150W, and 200W, and a color temperature of 4000K, allowing for perfect adaptation to the specific requirements of any space. Equipped with a 120x60° asymmetric lens, it minimizes light dispersion and allows for installation at greater heights, ensuring even illumination of the work surface.

With a high efficiency of 100 lm/W and a color rendering index of RA>80, STREAKBAY provides intense, natural light that improves working comfort and reduces eye strain.



Beam angle



Ambient temperature suitable for operation



Lifespan



Voltage range and voltage type



LED type




LED quantity

Parameter	Value
Luminous efficacy	100 lm/W
Power	150 W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	15000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	65
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	36 000
Weight	2100 g
Supply voltage range and voltage type	220-240V AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %


Parameter	Value
Beam angle	120x60 °
Material (cover)	polycarbonate
Material (housing)	DIE-CAST alu
LED type	SMD LED
LED quantity	162
Power Factor	0,95
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40÷40 °C
For indoor and outdoor use	YES
IEC protection class	I
IK protection rating	08
Length	827 mm
Width	118 mm
Height	78 mm
Product weight with packaging	2390 g

Single packaging




Width 827 mm
 Height 78 mm
 Length 118 mm
 Weight 2,12 kg
 1

Bulk packaging



Number of pieces/tape in meters pack 5 szt.
 Width 890 mm
 Height of collective packaging 162 mm
 Length 505 mm
 Weight 13,1 kg
 Volume 0,072 m³

Europallet



Quantity collective euro pallet 60 szt.
 Weight of a euro pallet 157,2 kg
 Pallet height 1944 mm
 Quantity in 1 layer 5 szt.
 Number of layers 12