


LED line PRIME

Code: 205864

EAN: 5905378205864

**Backlit Panel 4000K 34W 4760lm IP20  
60x60cm white UGR<19 PRIME 0-10V**



Backlit LED line PRIME panel with a power of 34W and a light color of 4000K is a modern solution that stands out for its high quality of workmanship and a luminous flux of 4760 lumens. The use of SMD LED 2835 technology ensures a luminous efficiency of 140 lm/W. The fixture features a low UGR<19, which affects lighting comfort. The solid aluminum housing guarantees durability and resistance to damage, and the L70B50 lifespan is 70.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 34 W
Voltage	• 200-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	0
Survival factor	0.9

Parameter	Value
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	30
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene


LED line PRIME

Code: 205864

EAN: 5905378205864


**Backlit Panel 4000K 34W 4760lm IP20  
60x60cm white UGR<19 PRIME 0-10V**

**Technical drawing**






**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	30 mm
Height	640 mm
Length	600 mm
Weight	1,53 kg

**Bulk packaging**

Quantity	5
Width	170 mm
Height	655 mm
Length	615 mm
Volume	0,075 m3
Weight	10,4 kg
Comments	

**Europallet**

Height	1340 mm
Quantity in layer	30
Number of layers	2
Bulk quantity	60
Weight	124,8 kg

---

LED line PRIME

Code: 205864

EAN: 5905378205864

**Backlit Panel 4000K 34W 4760lm IP20  
60x60cm white UGR<19 PRIME 0-10V**

---

**Example application**