

LED line PRIME

Code: 200180-SKY

EAN: 5905378218437

LED line PRIME Panel Backlit 40W
4000K 4800lm 595x595



The 40W backlit panel from LED line PRIME is a modern light source with a power of 40 W and a light stream of 4800 lm. It is characterized by a neutral colour of light 4000 K, which provides comfortable lighting. Thanks to the use of SMD LED technology and high light efficiency of 120 lm/W, it guarantees energy efficiency of E level and long-term durability, reaching up to 75000 hours of operation.



Technical data

| Parameter | Value |
|---------------------------------------|----------------|
| Voltage | • 220-240 V AC |
| Luminous efficacy | 120 |
| Colour of the light | White |
| Energy efficiency class 2019/2015 | E |
| Luminous flux | 4800 |
| Colour consistency in McAdam ellipses | ≤6 |
| Warranty (years) | 5 |
| IP protection rating | IP20 |
| Survival factor | 0.9 |
| Lifetime L70B50 | 75 000 h |
| Frequency of the supply voltage | 50/60Hz |
| Colour rendering index Ra | 80 |
| Colour | white |
| The lumen maintenance factor | 96 |
| Beam angle | 120 |

| Parameter | Value |
|--|--------------|
| Material (cover) | polystyrene |
| Material (housing) | Aluminium |
| LED type | SMD LED 2835 |
| LED quantity | 48 |
| Power Factor | 0,9 |
| Number of on/off cycles | 25000 |
| Colour consistency in McAdam ellipses | ≤6 |
| Ambient temperature suitable for operation | -25÷45 |
| For indoor use | Inside |
| IEC protection class | II |
| IK protection rating | 02 |
| Lamp's warm-up time to 60% | 1 s |
| Energy class | A+ |
| Correlated colour temperature | • 4000 K |
| Power | • 40 W |

LED line PRIME

Code: 200180-SKY



EAN: 5905378218437

**LED line PRIME Panel Backlit 40W
4000K 4800lm 595x595**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 200180-SKY

EAN: 5905378218437

**LED line PRIME Panel Backlit 40W
4000K 4800lm 595x595**

Example application

