

LED line PRIME

Code: 200180-DALI

EAN: 5905378218666

Backlit Panel 4000K 40W 4800lm IP20
60x60cm white PRIME DALI



Backlit panel 40W 4000K 4800lm 60x60 DALI PRIME from LED line PRIME is an advanced lighting solution with high performance. By emitting a light stream of 4,800 lumens at only 40 watts, the panel provides excellent energy efficiency at class E level. Thanks to the colour of the light 4000 K, it is ideal for different interior applications.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	120
Luminous flux	4800
The lumen maintenance factor	96
Lifetime L70B50	75 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	Dali
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	48
Power Factor	0,9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene
DALI	• YES

LED line PRIME

Code: 200180-DALI



EAN: 5905378218666

Backlit Panel 4000K 40W 4800lm IP20
60x60cm white PRIME DALI




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	30 mm
Height	640 mm
Length	600 mm
Weight	1,41 kg

Bulk packaging

Quantity	5
Width	170 mm
Height	655 mm
Length	615 mm
Volume	0,075 m3
Weight	9,6 kg
Comments	

Europallet

Quantity	80
Height	1880 mm
Quantity in layer	
Number of layers	
Bulk quantity	16
Weight	180 kg

LED line PRIME

Code: 200180-DALI

EAN: 5905378218666

**Backlit Panel 4000K 40W 4800lm IP20
60x60cm white PRIME DALI**

Example application

