

LED line PRIME

Code: 203709

EAN: 5905378203709

**LINKER TRI-PROOF 30W 4000K  
150lm/W 220-240V IP65 120cm PRIME**



**Technical data**

| Parameter                             | Value         |
|---------------------------------------|---------------|
| ULOR                                  | 3 %           |
| Luminous efficacy                     | 150 lm/W      |
| Colour of the light                   | White         |
| Energy efficiency class 2019/2015     | D             |
| Luminous flux                         | 4500 lm       |
| Colour consistency in McAdam ellipses | ≤6            |
| IP protection rating                  | IP65          |
| Warranty (years)                      | 5             |
| Survival factor                       | 0.9           |
| Lifetime L70B50                       | 100 000       |
| Frequency of the supply voltage       | 50/60Hz       |
| Colour rendering index Ra             | 80            |
| The lumen maintenance factor          | 96 %          |
| Beam angle                            | 120 °         |
| Material (cover)                      | polycarbonate |
| Material (housing)                    | Polycarbonate |
| LED type                              | SMD2835       |

| Parameter                                  | Value          |
|--------------------------------------------|----------------|
| Lifespan                                   | 100000         |
| Power Factor                               | 0,95           |
| Number of on/off cycles                    | 50000          |
| Colour consistency in McAdam ellipses      | ≤6             |
| Ambient temperature suitable for operation | -25÷45 °C      |
| For indoor and outdoor use                 | YES            |
| IEC protection class                       | II             |
| IK protection rating                       | 08             |
| Full box quantity                          | 4 pc           |
| Lamp's warm-up time to 60%                 | 1              |
| Length                                     | 1180 mm        |
| Width                                      | 72 mm          |
| Height                                     | 61 mm          |
| Energy class                               | A+             |
| Power                                      | • 30 W         |
| Voltage                                    | • 220-240 V AC |
| Correlated colour temperature              | • 4000 K       |

LED line PRIME

Code: 203709


EAN: 5905378203709

LINKER TRI-PROOF 30W 4000K  
150lm/W 220-240V IP65 120cm PRIME


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

|        |            |
|--------|------------|
| Width  | 1180 mm    |
| Height | 61 mm mm   |
| Length | 72 mm mm   |
| Weight | 1,43 kg kg |



Bulk packaging

|                                         |             |
|-----------------------------------------|-------------|
| Number of pieces/tape in meters pack zb | 15          |
| Width                                   | 1538 mm mm  |
| Height of collective packaging          | 288 mm      |
| Length                                  | 246 mm mm   |
| Weight                                  | 17,51 kg kg |
| Volume                                  | 0,108 m3 m3 |



Europallet

|                                              |               |
|----------------------------------------------|---------------|
| Number of pieces/tapes in meters euro pallet | 180           |
| Quantity collective euro pallet              | 180           |
| Weight of a euro pallet                      | 1260,72 kg kg |
| Pallet height                                | 1728 mm       |
| Quantity in 1 layer                          | 180           |
| Number of layers                             | 1             |

---

LED line PRIME

Code: 203709

EAN: 5905378203709

**LINKER TRI-PROOF 30W 4000K  
150lm/W 220-240V IP65 120cm PRIME**

---

**Example application**