

LED line PRIME

Code: 218574-DALI

EAN: 5905378227408

**Ceiling Light LEDIS 3CCT(3K/4K/6K)
12/16W 1600lm round IP65 white PRIME
DALI**



LEDIS ceiling with a power of 16W from the brand LED line **PRIME** is an excellent solution for lighting outdoor and indoor spaces. The choice of color temperature in the ranges **3000 K, 4000 K, and 6000 K** allows for adaptation to the character of the surroundings.

DALI version.

Product made to order - delivery within 10 days.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 16 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 6000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	II
Luminous efficacy	100
Luminous flux	1600
The lumen maintenance factor	96
Lifetime L70B50	35 000 h
Survival factor	0.9
Dimmable function	Dali
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	182
Lifespan	35 000 h
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷35
Installation method	surface
Height	85
Fixture's diameter	320
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate

DALI • YES


LED line PRIME

Code: 218574-DALI


EAN: 5905378227408

**Ceiling Light LEDIS 3CCT(3K/4K/6K)
12/16W 1600lm round IP65 white PRIME
DALI**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	320 mm
Height	320 mm
Length	85 mm
Weight	1,0 kg

Bulk packaging

Quantity	6
Width	700 mm
Height	320 mm
Length	320 mm
Volume	0,072 m3
Weight	
Comments	

Europallet

Quantity	
Height	
Quantity in layer	
Number of layers	
Bulk quantity	
Weight	

LED line PRIME

Code: 218574-DALI

EAN: 5905378227408

**Ceiling Light LEDIS 3CCT(3K/4K/6K)
12/16W 1600lm round IP65 white PRIME
DALI**

Example application