

LED line PRIME

Code: 210240

EAN: 5905378210240

Waterproof fixture RANGER 25-55W CCT
8250lm 150cm IP66 PRIME

New



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	150 lm/W	LED type	SMD2835
Colour of the light	White	LED quantity	392
Energy efficiency class 2019/2015	D	Power Factor	0,9
Luminous flux	8250 lm	Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6	Colour consistency in McAdam ellipses	≤6
IP protection rating	IP66	Ambient temperature suitable for operation	-25÷45 °C
Warranty (years)	5	For indoor and outdoor use	YES
Survival factor	0.9	IEC protection class	II
Lifetime L70B50	100 000	IK protection rating	10
Weight	1540 g	Full box quantity	9 pc
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	70	Length	1510 mm
Colour	Grey	Width	79 mm
The lumen maintenance factor	96 %	Height	68 mm
Beam angle	120 °	Power	25-55 W
Material (cover)	polycarbonate	Correlated colour temperature	3000 K 4000 K 5000 K
Material (housing)	Polycarbonate		

LED line PRIME


Code: 210240

EAN: 5905378210240

Waterproof fixture RANGER 25-55W CCT
8250lm 150cm IP66 PRIME

Dimensions


Light distribution




Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

Number of pieces/tape in meters pack zb 9

LED line PRIME

Code: 210240

EAN: 5905378210240

**Waterproof fixture RANGER 25-55W CCT
8250lm 150cm IP66 PRIME**

Example application