

LED line LITE

Code: 202825

EAN: 5905378202825

**DOWNLIGHT EASY FIX PRO
3CCT(3K/4K/5K) 6W 540lm round IP20
White LITE**



LED line panel LITE Downlight EASY FIX PRO 6W generates 540 lm light stream, offering light color adjustment in the range 3000-5000K. Thanks to the SMD2835 technology used and the high Ra>80 colour reproduction factor, it provides excellent color mapping. It offers flexibility for both surface and surface mounting, making it ideal for various lighting projects.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 6 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	90
Luminous flux	540
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Dimmable function	-

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD2835
LED quantity	112
Power Factor	0,7
Number of on/off cycles	20000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	55-100
Height	19,5
Fixture's diameter	140 mm
Colour	White
Material (cover)	Polycarbonate


LED line LITE

Code: 202825


EAN: 5905378202825

**DOWNLIGHT EASY FIX PRO
3CCT(3K/4K/5K) 6W 540lm round IP20
White LITE**


Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	160 mm
Height	42 mm
Length	147 mm
Weight	0,28 kg

Bulk packaging

Quantity	60
Width	432 mm
Height	334 mm
Length	460 mm
Volume	0,066 m3
Weight	18,6 kg
Comments	

Europallet

Height	1840 mm
Quantity in layer	240
Number of layers	4
Bulk quantity	960
Weight	297,6 kg

LED line LITE

Code: 202825

EAN: 5905378202825

DOWNLIGHT EASY FIX PRO
3CCT(3K/4K/5K) 6W 540lm round IP20
White LITE

Example application