

LED line LITE

Code: 247897

EAN: 5901583247897

**LED bulb E14 4000K 2W 130lm 230V  
270° T25 PC LITE**



LED bulb E14 2W 4000K from LED line LITE is a modern, energy-efficient light source with a stream of 130 lumens and light output of 65 lm/W. Thanks to the neutral white color (4000 K), it provides optimal visibility in different rooms. Equipped with a standard E14 thread, it easily fits into different frames. Its durability is 50,000 hours of operation, and Ra  $\geq$ 80 colour reproduction rate guarantees the natural appearance of illuminated objects.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	3
Power	• 2 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	65
Luminous flux	130 lm
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 $\approx$ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	$\leq$ 6
Frequency of the supply voltage	50/60Hz
Beam angle	270 °
Lifespan	50 000 h
Power Factor	0,8
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	50
Fixture's diameter	23 mm
Material (housing)	Polycarbonate

LED line LITE

Code: 247897

EAN: 5901583247897

**LED bulb E14 4000K 2W 130lm 230V  
270° T25 PC LITE**




Technical drawing

Light distribution

Additional product photos



Logistics data



**Single packaging**

Quantity	1
Width	25 mm
Height	25 mm
Length	55 mm
Weight	0,01 kg

**Bulk packaging**

Quantity	500
Width	730 mm
Height	290 mm
Length	150 mm
Volume	0,031 m3
Weight	5,795 kg
Comments	

**Europallet**

Quantity	20000
Height	1740 mm
Quantity in layer	4000
Number of layers	6
Bulk quantity	24000
Weight	278,16 kg

---

LED line LITE

Code: 247897

EAN: 5901583247897

**LED bulb E14 4000K 2W 130lm 230V  
270° T25 PC LITE**

---

**Example application**