

LED line PRIME

Code: 471093

EAN: 5907777471093

LED line® strip 700 SMD 24V 2200-3000K 12W DIM

ATG F



Technical data

Parameter	Value	Parameter	Value
Colour of the light	CCT-2pin	LED type	SMD2835
Energy efficiency class 2019/2015	F	Compatible dimmer type	PWM
Colour consistency in McAdam ellipses	≤3	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	2
Warranty (years)	5	Cutting section	10
Dimmable function	PWM	Type of adhesive tape	3M 300 LSE
Survival factor	0.9	Colour consistency in McAdam ellipses	≤3
Minimum purchase quantity	5	Ambient temperature suitable for operation	-25÷45 °C
Lifetime L70B50	50 000	For indoor use	Inside
Current (Im)	0,5	IEC protection class	III
Colour rendering index Ra	80	Width	10 mm
Metres per roll	5	Voltage	• 24 V DC
The lumen maintenance factor	96 %	Correlated colour temperature	• 2200-3000 K
Beam angle	120 °		

LED line PRIME

Code: 471093

EAN: 5907777471093

LED line® strip 700 SMD 24V 2200-3000K 12W DIM

Dimensions

Additional product photos



Logistics data

Single packaging

Number of pieces/tape in meters pack zb	100
---	-----

Bulk packaging

Number of pieces/tapes in meters euro pallet	2400
Quantity collective euro pallet	60
Weight of a euro pallet	300 kg
Pallet height	1800
Quantity in 1 layer	6
Number of layers	10

Europallet

LED line PRIME

Code: 471093

EAN: 5907777471093

**LED line® strip 700 SMD 24V 2200-
3000K 12W DIM**

Example application