

LED line PRIME

Code: 205819-AW3HAT

EAN: 5905378216617

Backlit 34W 4000K 4760lm 60x60
emergency module 3h autotest PRIME



The backlit LED panel with 34W power and 4000K light colour provides a high luminous flux of 4760 lm. Made of aluminium and polystyrene, it is characterized by a low rate of flickering, which affects comfort of use. Energy class C and Ra colour reproduction factor at level 80 guarantee the efficiency and quality of lighting. The panel is equipped with an emergency module running up to 3 hours with autotest function.



Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	autotest
Voltage	<ul style="list-style-type: none">220-240 V AC
Luminous efficacy	140
Colour of the light	White
Energy efficiency class 2019/2015	C
Luminous flux	4760
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
IP protection rating	IP20
Dimmable function	Triac
Survival factor	0.9
Lifetime L70B50	50 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White

Parameter	Value
The lumen maintenance factor	96
Beam angle	90
Material (cover)	polystyrene
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	128
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	<ul style="list-style-type: none">4000 K
Power	<ul style="list-style-type: none">34 W

LED line PRIME

Code: 205819-AW3HAT

EAN: 5905378216617

**Backlit 34W 4000K 4760lm 60x60
emergency module 3h autotest PRIME**

Technical drawing

Light distribution

Additional product photos

Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 205819-AW3HAT

EAN: 5905378216617

**Backlit 34W 4000K 4760lm 60x60
emergency module 3h autotest PRIME**

Example application