

LED line PRIME

Code: 470577-II

EAN: 5905378206816

LED line PRIME Ceiling lamp LUNAR
16W 4000K 1600lm IP65 round



Technical data

Parameter	Value
Luminous efficacy	100 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1600 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP65
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	50 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %
Fixture's diameter	265
Beam angle	120 °
Material (cover)	polycarbonate
Material (housing)	Polycarbonate

Parameter	Value
LED type	SMD2835
LED quantity	140
Lifespan	50000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40÷45 °C
For indoor and outdoor use	YES
IEC protection class	II
IK protection rating	10
Full box quantity	10 pc
Lamp's warm-up time to 60%	1
Height	40 mm
Power	• 16 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K

LED line PRIME

Code: 470577-II


EAN: 5905378206816

LED line PRIME Ceiling lamp LUNAR

16W 4000K 1600lm IP65 round




Dimensions

Light distribution



Additional product photos

Logistics data



Single packaging

Width	270 mm
Height	270 mm mm
Length	50 mm mm
Weight	0,88 kg kg
	1

Bulk packaging

Number of pieces/tape in meters pack zb	10 szt.
Width	525 mm mm
Height of collective packaging	285 mm
Length	285 mm mm
Weight	9,15 kg kg
Volume	0,042 m3 m3

Europallet

Number of pieces/tapes in meters euro pallet	200
Quantity collective euro pallet	240 szt.
Weight of a euro pallet	219,6 kg kg
Pallet height	1710 mm
Quantity in 1 layer	40 szt.
Number of layers	6

LED line PRIME

Code: 470577-II

EAN: 5905378206816

**LED line PRIME Ceiling lamp LUNAR
16W 4000K 1600lm IP65 round**

Example application