


LED line® E14 2W 4000K 250lm 180-265V FILAMENT C35



Product contains a graphene substrate which extends the life of the light source, improving its luminous efficiency, and thanks to its high flexibility qualities, creates an elliptical shape of the light source with a wide beam angle of 320°.



Manufacturer issues a 3-year warranty for this product.



Product combines the traditional vintage-style appearance with the modern LED technology.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation




LED type




Lifespan

Parameter	Value
Luminous efficacy	125 lm/W
Power	2 W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	250 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	180-265 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Lamp's diameter	35

Parameter	Value
Beam angle	320 °
Material (cover)	glass
LED type	FILAMENT
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	98 mm
Product weight with packaging	30 g
Master carton weight (kg)	3
Energy class	A++




Single packaging



1

Bulk packaging



100

Europallet

