


### Code: 244339 EAN: 5901583244339

# LED line® UFO T-Series 100-277V 100W 15000LM 4000K 120° DIM





High luminous efficacy ensured by high quality CREE branded LEDs.



This product is equipepd with a MEANWELL branded driver which ensures reliable and fault-free operation even during prolonged, continous running.

FLICKER FREE™ system guarantees no harmful flickering

effect and ensures safety for users' eyesight.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



DIMMABLE

voltage

00-277 VA

SMD3030

144

Parameter Material (housing)

\*.IES

Manufacturer issues a 5-year warranty for this product.



The power supply system used allows for smooth adjustment of light intensity using an appropriate dimmer.

Voltage range and voltage type

LED type

LED quantity



мах

-40÷45 °0

Beam angle

Ambient temperature suitable for operation

50 000 () L70B50

Lifespan



Dimmable

Value
150 lm/W
100 W
White
D
15000 lm
4000 K
≤6
65
5
1-10
0.9
50 000
100-277 VAC
50/60Hz
70
black
96 %

LED type SMD3030 LED quantity 144 Not dimmable TAK 1-10V Compatible dimmer type 50000 Lifespan 0,95 Power Factor 50000 Number of on/off cycles Colour consistency in McAdam ellipses ≤6 Ambient temperature suitable for operation -40÷45 °C For indoor and outdoor use YES IEC protection class Ĩ IK protection rating 08 Full box quantity 1pc Lamp's warm-up time to 60% 1 Height 250 mm Product weight with packaging 3150 g


Value

aluminum




Lamp's diameter	200	Master carton weight (kg)	31,5
Beam angle	120 °	Energy class	A+
Material (cover)	polycarbonate		

## Luminous [cd/klm]



#### Single packaging



270 215 270


3,33 1

#### Bulk packaging



Number of pieces/tape in meters pack zb	1
Width	270
Height of collective packaging	215
Length	270
Weight	3,33
Volume	0,015

#### Europallet



Number of pieces/tapes in meters euro pallet	
Quantity collective euro pallet	56
Weight of a euro pallet	186,48
Pallet height	1649
Quantity in 1 layer	8
Number of layers	7