

LED line PRIME

Code: 220614

EAN: 5905378220614

**Street luminaire TOLENO Icl 4000K
50W 7500lm T2M1 IP66 Gray (RAL 9007)
CRI70 PRIME**



TOLENO is a two-chamber street luminaire made of high-pressure aluminum die-casting with a high IP66 tightness and IK09 mechanical impact resistance. Tool-free access, a knife switch, wide adjustment of the mounting bracket, and an integrated level speed up installation and service. The tempered glass cover, directional multi-lens matrices, high-efficiency diodes, and the ability to adjust the luminaire's power ensure optimal lighting parameters. The Zhaga interface and programmable DALI driver enable integration with control systems.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	B
Warranty	5/7*
Power	• 50 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	09
IEC protection class	I
Luminous efficacy	150
Luminous flux	7500
Lifetime L70B50	100 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	100000 h
L90B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	100000 h
Dimmable function	0-10
Frequency of the supply voltage	50/60Hz
Beam angle	T2M1
Power Factor	>0,95
Ambient temperature suitable for operation	-40 ÷ 45
For indoor use	Outside
Height	124 mm
Fixture's diameter	60 mm
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line PRIME

Code: 220614


EAN: 5905378220614

**Street luminaire TOLENO Icl 4000K
50W 7500lm T2M1 IP66 Gray (RAL 9007)
CRI70 PRIME**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Width	500 mm
Height	120 mm
Length	265 mm
Weight	3,12 kg

Bulk packaging

Quantity	1
Width	500 mm
Height	120 mm
Length	265 mm

Europallet

Quantity	72
Height	1900 mm
Quantity in layer	
Number of layers	
Bulk quantity	72
Weight	270 kg

LED line PRIME

Code: 220614

EAN: 5905378220614

**Street luminaire TOLENO Icl 4000K
50W 7500lm T2M1 IP66 Gray (RAL 9007)
CRI70 PRIME**

Example application