

LED line PRIME

Code: 203709-DALI

EAN: 5905378221536

**LINKER hermetic fixture 4000K 30W
4500lm IP65 120cm gray PRIME DALI**



LED line fixtures from the LINKER series are an energy-efficient solution for industry, medical facilities, and warehouses. Available in powers of 21-80W, they offer up to 150 lm/W and the possibility of serial connection (up to 22 units). High luminous efficiency reduces energy and maintenance costs, providing durable and effective lighting.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	150
Luminous flux	4500
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	75000 h

Parameter	Value
L90B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	50000 h
Dimmable function	Dali
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2836
Lifespan	100 000 h
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25 ÷ 45
Height	61 mm
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate
DALI	• YES


LED line PRIME

Code: 203709-DALI

EAN: 5905378221536

**LINKER hermetic fixture 4000K 30W
4500lm IP65 120cm gray PRIME DALI**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	75 mm
Height	65 mm
Length	1120 mm
Weight	1,64 kg

Bulk packaging

Quantity	15
Width	288 mm
Height	246 mm
Length	1538 mm
Volume	
Weight	30,3 kg

Europallet

Quantity	180
Height	1500 mm
Quantity in layer	
Number of layers	
Bulk quantity	12
Weight	389 kg

LED line PRIME

Code: 203709-DALI

EAN: 5905378221536

**LINKER hermetic fixture 4000K 30W
4500lm IP65 120cm gray PRIME DALI**

Example application

