

LED line PRIME

Code: 479952

EAN: 5907777479952

LED line PRIME LED strip 128 SMD 24V
4000K 8,5W 160lm/W



product_card.label_technical_data

Parameter	Value
Luminous efficacy	160 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Colour consistency in MacAdam ellipses	≤3
IP protection rating	IP20
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wire length	200 mm
Wattage (lm)	8,5 W
Luminous flux (lm)	1360
Current (lm)	0,35
Colour rendering index Ra	80
Metres per roll	5
The lumen maintenance factor	96 %
Beam angle	120 °

Parameter	Value
LED type	SMD
LED quantity	640
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	3
LED quantity (lm)	128
Cutting section	6,25
Type of adhesive tape	3M 300 LSE
Colour consistency in MacAdam ellipses	≤3
Ambient temperature suitable for operation	-25÷45 °C
For indoor use	Inside
IEC protection class	III
Length	5000 mm
Width	10 mm
Height	2,5 mm
Power	• 8.5
Voltage	• 24 V DC
Correlated colour temperature	• 4000 K

LED line PRIME

Code: 479952


EAN: 5907777479952

LED line PRIME LED strip 128 SMD 24V
4000K 8,5W 160lm/W


product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	153 mm
Height	15 mm mm
Length	153 mm mm
Weight	0,14 kg
	5



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm mm
Height of collective packaging	180 mm
Length	320 mm mm
Weight	5,4 kg kg
Volume	0,020 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	349,0 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line PRIME

Code: 479952

EAN: 5907777479952

**LED line PRIME LED strip 128 SMD 24V
4000K 8,5W 160lm/W**

Example application