

LED line LITE

product_card.label_product_code: 246760
product_card.label_product_gtin: 5901583246760

LEDOM GU10 1W 6500K 120lm 220-240V



product_card.label_technical_data

product_card.label_attribute_name	product_card.label_attribute_value
Luminous efficacy	120 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	120 lm
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
Survival factor	0.9
Lifetime L70B50	25 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Lamp's diameter	50

product_card.label_attribute_name	product_card.label_attribute_value
Beam angle	100 °
Lifespan	25000
Power Factor	0,4
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Height	53 mm
Energy class	A+
Power	• 1 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 6500 K

LED line LITE

product_card.label_product_code: 246760
product_card.label_product_gtin: 5901583246760

LEDOM GU10 1W 6500K 120lm 220-240V




product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery



product_card.label_logistic_data



product_card.label_single_package

Width	1220 mm
Height	36 mm mm
Length	36 mm mm
Weight	0,03 kg kg
	1

product_card.label_collective_package

Number of pieces/tape in meters pack zb	100 szt.
Width	580 mm mm
Height of collective packaging	255 mm
Length	175 mm mm
Weight	6,5 kg kg
Volume	0,025 m3 m3

product_card.label_europalette

Number of pieces/tapes in meters euro pallet	4400
Quantity collective euro pallet	5600 szt.
Weight of a euro pallet	364 kg kg
Pallet height	1785 mm
Quantity in 1 layer	800 szt.
Number of layers	7

LED line LITE product_card.label_product_code product_card.label_product_gtin: 246760 5901583246760

LEDOM GU10 1W 6500K 120lm 220-240V

product_card.label_realization_photo