

LED line PRIME

Code: 479587-CAW3HAT

EAN: 5905378218147

LINKER TRI-PROOF 21W 4000K 3150lm
150lm/W IP65 60cm Emergency module
3H AT CNBOP PRIME



LINKER is a 21 W high-performance LED luminaire that generates a luminous flux of 3150 lm, which translates into energy efficiency of 150 lm/W. Thanks to the colour of the light 4000 K provides neutral lighting. The product is characterized by IP65 leak class, which guarantees full protection against water and dust. The emergency operation time is up to 3 hours. LINKER has a durability of up to 100,000 hours and a light stream performance of 96%.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	<ul style="list-style-type: none">21 W
Voltage	<ul style="list-style-type: none">220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none">4000K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IEC protection class	II
Luminous efficacy	150
Luminous flux	3150
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
ULOR	3 %
Emergency module test	Autotest
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	120
Lifespan	100 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-25 ÷ 45
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	polycarbonate

LED line PRIME

Code: 479587-CAW3HAT

EAN: 5905378218147


**LINKER TRI-PROOF 21W 4000K 3150lm
150lm/W IP65 60cm Emergency module
3H AT CNBOP PRIME**

Technical drawing


Light distribution

Additional product photos


Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 479587-CAW3HAT

EAN: 5905378218147

**LINKER TRI-PROOF 21W 4000K 3150lm
150lm/W IP65 60cm Emergency module
3H AT CNBOP PRIME**

Example application