

LED line PRIME

product_card.label_product_codeproduct_card.label_product_gtin:
LL-35-245907777479211

LED power supply LED line PRIME LL-35-24 IP67 24V



product_card.label_technical_data

product_card.label_attribute_name	product_card.label_attribute	product_card.label_attribute_name	product_card.label_attrib
Output current range	0 ÷ 1,5A	Insulation strength	3kVAC
Warranty (years)	5	EMC standards	EN55015
Input voltage frequency range	47 ÷ 63Hz	Mounting type	surface
Rated current	1,5A	Inrush current (typ.)	70A / 230VAC
Safety standards	IP67	Ambient temperature suitable for operation	-30÷50 °C
Efficiency	0,85	IEC protection class	II
Voltage tolerance	-/+5,0%	Power	• 36 W
Ambient humidity	20 ÷ 90%	Voltage	• 90-264 V AC

LED line PRIME


product_card.label_product_code: LL-35-24
product_card.label_product_gtin: 5907777479211

LED power supply LED line PRIME LL-35-24 IP67 24V




product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery



product_card.label_logistic_data



product_card.label_single_package

Width	45
Height	30 mm
Length	165 mm
Weight	0,24 kg
	1

product_card.label_collective_package

Number of pieces/tape in meters pack zb	80
Width	240 mm
Height of collective packaging	260
Length	345 mm
Weight	20,5 kg

product_card.label_europalette

Number of pieces/tapes in meters euro pallet	2880
Quantity collective euro pallet	36
Weight of a euro pallet	748 kg
Pallet height	1060

LED line PRIME

product_card.label_product_codeproduct_card.label_product_gtin:
LL-35-245907777479211

LED power supply LED line PRIME LL-
35-24 IP67 24V

product_card.label_realization_photo