

LED line PRIME

Code: LL-35-24

EAN: 5907777479211

**Power Supply 35-24 IP67 36W 24V PRIME**

The PRIME 35-24 IP67 24V LED line power supply is a specialized device with 36W power and 24V output voltage, perfectly adapted for operation in difficult outdoor conditions with IP67 protection class. Its input voltage range ranges from 90 to 264V AC, which provides specialized flexibility in applications. With a high efficiency of 85% and a power factor of 0.95, it guarantees efficient operation and minimizes energy losses.



**Technical data**

Parameter	Value
Warranty	5
Power	• 36 W
Voltage	• 90-264 V AC
IEC protection class	II
Output current range	0 ÷ 1,5A
Input voltage frequency range	47 ÷ 63Hz
Rated current	1,5A
Safety standards	IP67
Efficiency	0,85

Parameter	Value
Voltage tolerance	-/+5.0%
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	70A / 230VAC
Ambient temperature suitable for operation	-30÷40
Height	30 mm
Output voltage	• 24 V


LED line PRIME

Code: LL-35-24

EAN: 5907777479211


**Power Supply 35-24 IP67 36W 24V  
PRIME**

**Technical drawing**






**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	45 mm
Height	30 mm
Length	165 mm
Weight	0,24 kg

**Bulk packaging**

Quantity	50
Width	240 mm
Height	260 mm
Length	345 mm
Weight	16,8 kg

**Europallet**

Quantity	2880
Height	1060 mm
Bulk quantity	36
Weight	748 kg

---

LED line PRIME

Code: LL-35-24

EAN: 5907777479211

**Power Supply 35-24 IP67 36W 24V  
PRIME**

---

**Example application**