

LED line PRIME Code: 203457-LAW3HAT EAN: 5905378218345

Panel Backlit 42W 4000K 6300lm UGR<19 60x60 Emergency module PRIME LAW3HAT



The 42W backlit LED panel and 4000K colour temperature provide exceptional light performance, reaching a light stream of 6300 lm. With low UGR value<19, this model minimizes glare. Made of high quality aluminum and polystyrene, it guarantees longevity and aesthetic appearance. The integrated emergency module allows to operate for 3 hours in case of power interruption.





Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	Auto Test
Voltage	• 220-240 V AC
Luminous efficacy	150
Colour of the light	White
Energy efficiency class 2019/2015	В
Luminous flux	6300
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
IP protection rating	IP20
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	50 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White

Parameter	Value
The lumen maintenance factor	96
Beam angle	90
Material (cover)	polystyrene
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	108
Power Factor	0,9
Number of on/off cycles	25000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	ls
Correlated colour temperature	• 4000 K
Power	• 42 W



LED line PRIME Code: 203457-LAW3HAT EAN: 5905378218345


Panel Backlit 42W 4000K 6300Im UGR<19 60x60 Emergency module PRIME LAW3HAT

PRIME LAW3HAT

Technical drawing

Light distribution

Additional product photos












Logistics data







Single packaging

Bulk packaging

Europallet

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 203457-LAW3HAT EAN: 5905378218345

Panel Backlit 42W 4000K 6300Im UGR<19 60x60 Emergency module PRIME LAW3HAT

Example application