


LED line® E27 7W 4000K 630lm 170-250V G45

The structural design of this product ensures effective heat dissipation.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



LED type



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



Lamp type




Lifespan

Parameter	Value
Luminous efficacy	90 lm/W
Power	7 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	630 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	170-250 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96
Lamp's type	G45
Lamp's diameter	45
Beam angle	280 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835


Parameter	Value
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	82 mm
Product weight with packaging (g)	73 g
Master carton weight (kg)	7,3
EPREL ID	632128
Date of first placement on the market	01.04.2019
Energy class	A+
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	6
Total luminous flux (EPREL)	630
On-mode power Pon (EPREL)	7

Lifespan	30000
Power Factor	0,5

Useful luminous flux Φ_{use} (EPREL)	630
Beam angle in degrees (EPREL)	280




Single packaging




50
105
50
0,6
1

Bulk packaging



100

Europallet



6