

LED line® G9 4W 3000K 350lm 220-240V

Manufacturer issues a 3-year warranty for this product.



Beam angle



LED type



The structural design of this product ensures effective heat dissipation.



Voltage range and voltage type




Lifespan

Parameter	Value
Luminous efficacy	88 lm/W
Power	4 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	350 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96 %

Parameter	Value
Lamp's diameter	16
Beam angle	270 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,4
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	500 pc
Lamp's warm-up time to 60%	1
Height	49 mm
Product weight with packaging	16 g
Master carton weight (kg)	8
Energy class	A+

Luminous [cd/klm]




C0 - C180 C90 - C270

Single packaging



Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,01 kg

Bulk packaging



Number of pieces/tape in meters pack zb	500 szt.
Width	610 mm
Height of collective packaging	235 mm
Length	150 mm
Weight	7,455 kg
Volume	0,021 m ³

Europallet



Quantity collective euro pallet	32000 szt.
Weight of a euro pallet	477,12 kg
Pallet height	1880 mm
Quantity in 1 layer	4000 szt.
Number of layers	8