

LED line LITE

Code: 202887-SKY

EAN: 5905378218444

LED line LITE Panel Backlit 40W 4000K
4000lm 595x595



The LED line LITE Backlit 40W panel is a modern light source with a high light output of 4000 lumens. It is characterized by a colour temperature of 4000 K, which provides natural, white light. Its dimensions are 595 x 595 mm, and the thickness is only 28 mm, which facilitates installation in different spaces. The panel made of aluminium and polystyrene guarantees durability and aesthetic appearance.



Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	100
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	4000
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
IP protection rating	IP20
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	30 000 h
Working current	0,193
Dimmable	NO
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white

Parameter	Value
The lumen maintenance factor	96
Beam angle	120
Material (cover)	polystyrene
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	48
Power Factor	0,9
Number of on/off cycles	25000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
IEC protection class	I
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 40 W


LED line LITE

Code: 202887-SKY


EAN: 5905378218444

**LED line LITE Panel Backlit 40W 4000K
4000lm 595x595**

Technical drawing




Light distribution




Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line LITE

Code: 202887-SKY

EAN: 5905378218444

**LED line LITE Panel Backlit 40W 4000K
4000lm 595x595**

Example application

