

LED line PRIME

Code: 210622

EAN: 5905378210622

**Connector I linear for 3 phase track
LUMICANTO white with feeding PRIME**

The LUMICANTO white rail adapter I, powered by PRIME, is a modern solution for a stable connection in lighting installations. It is characterized by a working voltage of 220-240V AC and rated current 16A, which guarantees high efficiency and safety of use. The product made of plastic presents modern design, perfectly entering various arrangements.



Technical data

Parameter	Value
Warranty	5/7*
IEC protection class	I
Rated power	220-240V AC
Rated current	16A
Mounting type	3 phase rail
Frequency of the supply voltage	50/60Hz

Parameter	Value
Ambient temperature suitable for operation	5÷40
Height	32
Power supply connection	yes
Equivalent	XTS 14
Colour	White
Material (housing)	Plastic

LED line PRIME

Code: 210622

EAN: 5905378210622

**Connector I linear for 3 phase track
LUMICANTO white with feeding PRIME**


Technical drawing

Light distribution

Additional product photos




Logistics data




Single packaging

Width	170 mm
Height	30 mm
Length	30 mm
Weight	0,1 kg



Bulk packaging

Quantity	100
Width	250 mm
Height	220 mm
Length	400 mm
Volume	0,022 m3
Weight	10,4 kg



Europallet

Height	1760 mm
Quantity in layer	900
Number of layers	8
Bulk quantity	7200
Weight	367,2 kg

LED line PRIME

Code: 210622

EAN: 5905378210622

**Connector I linear for 3 phase track
LUMICANTO white with feeding PRIME**

Example application