


LED line® G9 4W 4000K 350lm 220-240V

The structural design of this product ensures effective heat dissipation.



Voltage range and voltage type



LED type



Manufacturer issues a 3-year warranty for this product.



Beam angle




Lifespan

Parameter	Value
Luminous efficacy	88 lm/W
Power	4 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	350 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	220-240 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96
Lamp's diameter	16
Beam angle	270 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,4


Parameter	Value
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	500 pc
Lamp's warm-up time to 60%	1
Height	49 mm
Product weight with packaging (g)	16 g
Master carton weight (kg)	8
EPREL ID	1 551 404
Energy class	A+
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tunable light source (EPREL)	No
R9 colour rendering index value (EPREL)	10
Total luminous flux (EPREL)	350
On-mode power P _{on} (EPREL)	4
Useful luminous flux Φ _{use} (EPREL)	350
Beam angle in degrees (EPREL)	270

Luminous [cd/klm]




C0 - C180 C90 - C270

Single packaging




20
62
20
1

Bulk packaging



500

Europallet



5