


LED line® GU10 10W 4000K 1000lm 170-250V

The structural design of this product ensures effective heat dissipation.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



Lifespan



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type




LED type




Parameter	Value
Luminous efficacy	100 lm/W
Power	10 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	1000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	170-250 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96
Lamp's diameter	50
Beam angle	120 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000

Parameter	Value
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	56 mm
Product weight with packaging (g)	72 g
Master carton weight (kg)	7,2
EPREL ID	632 098
Date of first placement on the market	01.02.2017
Energy class	A+
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	4
Total luminous flux (EPREL)	1 000
On-mode power Pon (EPREL)	10
Useful luminous flux Φuse (EPREL)	1 000
Beam angle in degrees (EPREL)	120




Single packaging




50
63
50
0,65
10

Bulk packaging



100

Europallet



4