

LED line PRIME

Code: LL-35-12

EAN: 5907777479204

Power Supply 35-12 IP67 36W 12V PRIME

The PRIME 35-12 IP67 12V LED line power supply is an advanced power supply with 36 W output, which provides a stable voltage of 12 V. Thanks to the IP67 leak class, the device is resistant to water and dust, which guarantees reliability in difficult weather conditions. The input voltage range is 90 to 265 V AC at 47-63 Hz.



5
WARRANTY

IP
67

PF
0,95

24V
DC

MAX
-30÷70°C

CE

Technical data

Parameter	Value	Parameter	Value
Warranty	5	Voltage tolerance	-/+5.0%
Power	• 36 W	Ambient humidity	20 ÷ 90%
Voltage	• 90-265 V AC	Insulation strength	3kVAC
IEC protection class	II	EMC standards	EN55015
Output current range	0 ÷ 3A	Mounting type	surface
Input voltage frequency range	47 ÷ 63Hz	Inrush current (typ.)	70A / 230VAC
Rated current	3A	Ambient temperature suitable for operation	-30÷50
Safety standards	IP67	Output voltage	• 12 V
Efficiency	0,82		


LED line PRIME

Code: LL-35-12

EAN: 5907777479204

Power Supply 35-12 IP67 36W 12V PRIME

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	45 mm
Height	30 mm
Length	165 mm
Weight	0,24 kg



Bulk packaging

Quantity	50
Width	240 mm
Height	260 mm
Length	345 mm
Weight	16,8 kg



Europallet

Quantity	2880
Height	1060 mm
Bulk quantity	36
Weight	748 kg

LED line PRIME

Code: LL-35-12

EAN: 5907777479204

Power Supply 35-12 IP67 36W 12V PRIME

Example application