

LED line PRIME

Code: 201330-010V

EAN: 5905378220201

Panel Backlit 40W 4000K 4800lm  
30x120cm 0-10V PRIME



**LED line PRIME Panel Backlit 40W** is an advanced lighting solution with a power of 40W, emitting white light with a temperature of 4000K and a luminous flux of 4800 lm. It has a beam angle of 120°, which ensures optimal light distribution. Made of aluminum and polystyrene, it features high-quality workmanship and a durability of up to 75,000 hours of operation. It offers a color rendering index Ra of 80, energy efficiency class D, and 0-10V control.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	120
Luminous flux	4800
The lumen maintenance factor	96
Lifetime L70B50	75 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤3
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	48
Power Factor	0,9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 201330-010V

EAN: 5905378220201

**Panel Backlit 40W 4000K 4800lm  
30x120cm 0-10V PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

---

LED line PRIME

Code: 201330-010V

EAN: 5905378220201

**Panel Backlit 40W 4000K 4800lm  
30x120cm 0-10V PRIME**

---

**Example application**