

LED line PRIME


Code: 201330-010V

EAN: 5905378220201

**Backlit Panel 4000K 40W 4800lm IP20
30x120cm white PRIME 0-10V**



LED line PRIME Panel Backlit 40W is an advanced lighting solution with a power of 40W, emitting white light with a temperature of 4000K and a luminous flux of 4800 lm. It has a beam angle of 120°, which ensures optimal light distribution. Made of aluminum and polystyrene, it features high-quality workmanship and a durability of up to 75,000 hours of operation. It offers a color rendering index Ra of 80, energy efficiency class D, and 0-10V control.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	120
Luminous flux	4800
The lumen maintenance factor	96
Lifetime L70B50	75 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤3
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	48
Power Factor	>=0,95
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Height	28
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 201330-010V

EAN: 5905378220201

**Backlit Panel 4000K 40W 4800lm IP20
30x120cm white PRIME 0-10V**




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	305 mm
Height	32 mm
Length	1240 mm
Weight	1,7 kg

Bulk packaging

Quantity	6
Width	330 mm
Height	240 mm
Length	1265 mm
Volume	0,100 m3
Weight	11,57 kg
Comments	

Europallet

Quantity	54
Height	1650 mm
Quantity in layer	
Number of layers	
Bulk quantity	9
Weight	113 kg

LED line PRIME

Code: 201330-010V

EAN: 5905378220201

**Backlit Panel 4000K 40W 4800lm IP20
30x120cm white PRIME 0-10V**

Example application