

LED line LITE Code: 200746 EAN: 5905378200746

LED line LITE Downlight MOLLY 5W 500lm 4000K round





LED line LITE Downlight MOLLY 5W and 500 lumen light stream is a modern solution in a minimalist style. Equipped with SMD LED technology 2835, it provides excellent light efficiency at 100 lm/W. It offers neutral light temperature 4000K and Ra>80 color rendering, which guarantees natural light effect.



















Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	100
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	500
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
IP protection rating	IP20
Survival factor	0.9
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96

Parameter	Value
Fixture's diameter	95 mm
Beam angle	110
Material (housing)	Polycarbonate
LED type	SMD LED 2835
LED quantity	16
Power Factor	0,5
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
Mounting hole diameter	75-90
For indoor use	Inside
IEC protection class	II
Correlated colour temperature	• 4000 K
Power	• 5W



LED line LITE Code: 200746 EAN: 5905378200746


LED line LITE Downlight MOLLY 5W 500lm 4000K round

Technical drawing



Light distribution

Luminous [cd/klm]



Additional product photos












Logistics data







Single packaging

Bulk packaging

Europallet



LED line LITE Code: 200746 EAN: 5905378200746

LED line LITE Downlight MOLLY 5W 500lm 4000K round

Example application

