

LED line PRIME

Code: 248115-II

EAN: 5905378201583

LED line PRIME LED bulb GU11 3W
4000K 330lm 170-250V 38°



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	110 lm/W	Lamp's diameter	35
Colour of the light	White	Beam angle	38 °
Energy efficiency class 2019/2015	F	Material (housing)	Ceramic
Luminous flux	330 lm	LED type	SMD2835
Colour consistency in McAdam ellipses	≤6	Lifespan	30000
IP protection rating	IP20	Power Factor	0,5
Warranty (years)	5	Number of on/off cycles	50000
Survival factor	0.9	Colour consistency in McAdam ellipses	≤6
Lifetime L70B50	30 000	For indoor use	Inside
Material	Ceramic	Full box quantity	100 pc
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	80	Height	50 mm
Colour	White	Power	• 3 W
The lumen maintenance factor	96 %	Voltage	• 170-250 V AC
Lamp's type	GU11	Correlated colour temperature	• 4000 K

LED line PRIME

Code: 248115-II

EAN: 5905378201583

LED line PRIME LED bulb GU11 3W
4000K 330lm 170-250V 38°


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	50 mm
Height	57 mm mm
Length	50 mm mm
Weight	0,03 kg kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	420 mm mm
Height of collective packaging	135 mm
Length	205 mm mm
Weight	5 kg kg
Volume	0,011 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	25000
Quantity collective euro pallet	8400 szt.
Weight of a euro pallet	420 kg kg
Pallet height	1890 mm
Quantity in 1 layer	600 szt.
Number of layers	14

LED line PRIME

Code: 248115-II

EAN: 5905378201583

**LED line PRIME LED bulb GU11 3W
4000K 330lm 170-250V 38°**

Example application