

LED line LITE

Code: 205604

EAN: 5905378205604

**Backlit Panel 2in1 4000K 40W 4000lm  
IP20 62x62cm black Surface-  
mounted/Recessed LITE**



The Backlit Panel 2in1 40W 4000K 4000LM is a LED line fixture of exceptional quality, offering an energy-efficient light source with a luminous flux of 4000 lm. The light color of 4000 K provides neutral, pleasant lighting. The IP20 protection class and high durability (L70B50: 30,000 h) make it an ideal solution for interiors.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	38 mm
Material (housing)	Metal
Material (cover)	Polystyrene


LED line LITE

Code: 205604

EAN: 5905378205604

**Backlit Panel 2in1 4000K 40W 4000lm  
IP20 62x62cm black Surface-  
mounted/Recessed LITE**

**Technical drawing**




**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Width	630 mm
Height	45 mm
Length	630 mm
Weight	1,67 kg

**Bulk packaging**

Quantity	6
Width	645 mm
Height	300 mm
Length	655 mm
Volume	0,128 m <sup>3</sup>
Weight	10,32 kg

**Europallet**

Height	1820 mm
Quantity in layer	24
Number of layers	2
Bulk quantity	48
Weight	82,56 kg

---

LED line LITE

Code: 205604

EAN: 5905378205604

**Backlit Panel 2in1 4000K 40W 4000lm  
IP20 62x62cm black Surface-  
mounted/Recessed LITE**

---

Example application