

LED line PRIME

Code: LL-75-24

EAN: 5907777479235

Power Supply 75-24 IP67 75W 24V PRIME



The PRIME 75-24 IP67 LED line power supply is an advanced device with an output power of 72 W, designed to power LED systems. It is characterized by a wide range of input voltage from 90 to 264 V AC and a stable output voltage of 24 V. Its effectiveness is 0.86 and the power factor PF is 0.95. The IP67 leak class housing used provides resistance to water and dust, making it an ideal choice for difficult operating conditions.



Technical data

Parameter	Value
Warranty	5
Power	• 75 W
Voltage	• 90-264 V AC
IEC protection class	II
Output current range	0 ÷ 3,13 A
Input voltage frequency range	50 ÷ 60Hz
Rated current	0,343
Safety standards	IP67
Efficiency	0,86
Voltage tolerance	-/+5.0%

Parameter	Value
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	70A / 230VAC
Power Factor	>=0,95
Ambient temperature suitable for operation	-30÷50
Height	32 mm
Output voltage	• 24 V


LED line PRIME

Code: LL-75-24

EAN: 5907777479235


**Power Supply 75-24 IP67 75W 24V
PRIME**

Technical drawing





Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	52 mm
Height	35 mm
Length	185 mm
Weight	0,42 kg

Bulk packaging

Quantity	50
Width	275 mm
Height	195 mm
Length	385 mm
Weight	22 kg

Europallet

Quantity	2400
Height	1,90 m
Quantity in layer	400
Number of layers	6
Bulk quantity	48
Weight	1100 kg

LED line PRIME

Code: LL-75-24

EAN: 5907777479235

**Power Supply 75-24 IP67 75W 24V
PRIME**

Example application