




Code: 479747 EAN: 5907777479747

## LED line PRIME LED strip 320 COB 24V 6500K 8W IP66

**LED Strip line** is a modern and versatile linear **light source**, used for interior lighting, furniture, lightboxes, illuminated signs, and public spaces.





Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.

The colour temperature range of the product falls within 3

steps of MacAdam formula, which ensures high consistency of



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years.

Manufacturer issues a 5-year warranty for this product.

**3**-step MacAdam

180 °

ΜΑΧ

-30÷45 °C

Beam angle

the produced light.

Ambient temperature suitable for operation

50 000 () L70B50

Lifespan



LED quantity (1m)

Parameter	Value
Luminous efficacy	100 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	F
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤3
IP protection rating	66
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wire length	200 mm
Wattage (1m)	8 W
Luminous flux (1m)	800
Current (1m)	0,33
Supply voltage range and voltage type	24 VDC

LED line PRIME® export@ledline.pl www.ledline.eu

Wygenerowano 12-03-2025 godz 05:03 z systemu PIM B2B - LED Line



voltage

1600

Voltage range and voltage type



- - -

LED type

LED quantity


Parameter	Value
The lumen maintenance factor	96 %
Beam angle	180 °
LED type	СОВ
LED quantity	1600
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (Im)	320
Cutting section	5
Type of adhesive tape	3M 300 LSE
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-30÷45 °C
For indoor use	Inside
IEC protection class	Ш
Length	5000 mm
Width	9 mm



Colour rendering index Ra	90
Metres per roll	5




## Single packaging



Height Length Weight 180 mm 20 mm 180 mm 0,21 kg


5

## Bulk packaging



Number of pieces/tape in meters pack40 szt.zb460 mmWidth460 mmHeight of collective packaging210 mmLength380 mmWeight8,7 kgVolume0,036<br/>m3

## Europallet



Number of pieces/tapes in meters euro pallet	7200 m
Quantity collective euro pallet	1440 szt.
Weight of a euro pallet	259,9
Pallet height	1890 mm
Quantity in 1 layer	160 szt.
Number of layers	9