

LED line PRIME

Code: 205833

EAN: 5905378205833

LED line PRIME Panel Backlit 34W
4000K 4760lm UGR<19 595x595



The PRIME LED line panel is an advanced 34W lighting luminaire, generating an impressive light stream of 4760 lm. It is characterized by the colour of 4000K light and highly effective SMD LEDs 2835, which provides a illumination with a capacity of 140 lm/W. Ugr<19 guarantees low glare, and a solid aluminium and polystyrene housing ensures durability. The product has a long life of L70B50 at level 70.



Technical data

Parameter	Value
Voltage	• 200-240 V AC
Luminous efficacy	140
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	4760
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
IP protection rating	IP20
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	50 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96

Parameter	Value
Beam angle	90
Material (cover)	polystyrene
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 34 W

LED line PRIME

Code: 205833

EAN: 5905378205833

**LED line PRIME Panel Backlit 34W
4000K 4760lm UGR<19 595x595**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 205833

EAN: 5905378205833

**LED line PRIME Panel Backlit 34W
4000K 4760lm UGR<19 595x595**

Example application

