

LED line LITE

Code: 477644

EAN: 5907777477644

**Tri-proof hermetic fixture 4000K 30W
3600lm IP65 65cm gray LITE PIR**



TRI-PROOF LED line LITE 30W 4000K 650 mm long is an innovative product with high light performance of 3600 lm. The PF power factor of 0.9 and energy efficiency class E confirm its savings. Thanks to the PIR motion sensor range up to 8 meters and resistance to atmospheric conditions (IP65), it is ideal in difficult environments.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 30 W
Voltage	• 185-265 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	II
Luminous efficacy	120
Luminous flux	3600
The lumen maintenance factor	96
Lifetime L70B50	35 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Standby power	0,5

Parameter	Value
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	70 lx
Mounting type	surface
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
LED type	2835
LED quantity	96
Lifespan	35 000 h
Power Factor	0,9
Number of on/off cycles	20000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Height	60 mm
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line LITE

Code: 477644


EAN: 5907777477644

**Tri-proof hermetic fixture 4000K 30W
3600lm IP65 65cm gray LITE PIR**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	650 mm
Height	60 mm
Length	82 mm
Weight	0,4 kg

Bulk packaging

Quantity	10
Width	330 mm
Height	190 mm
Length	660 mm
Volume	0,041 m3
Weight	7,35 kg
Comments	

Europallet

Quantity	300
Height	1,8 m
Quantity in layer	60
Number of layers	5
Bulk quantity	30
Weight	250 kg

LED line LITE

Code: 477644

EAN: 5907777477644

**Tri-proof hermetic fixture 4000K 30W
3600lm IP65 65cm gray LITE PIR**

Example application