


## LED line LITE TRI-PROOF 30W 4000K 650mm PIR



For indoor and outdoor use



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Flicker Free



Voltage range and voltage type



LED type



LED quantity



The "fast-connect" fitting allows the user to connect power to the lamp in timely and easy manner and guarantees a waterproof protection of the power cable connection.



Manufacturer issues a 3-year warranty for this product.



Beam angle



Ambient temperature suitable for operation



Lifespan


Parameter	Value
Luminous efficacy	120 lm/W
Colour of the light	White
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	70 lx
Energy efficiency class 2019/2015	E
Luminous flux	3600 lm
Colour consistency in McAdam ellipses	≤6
Standby power	0,5 uW
IP protection rating	IP65
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	35 000
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
CRI colour rendering index	80
Colour	White
The lumen maintenance factor	96 %
Beam angle	120 °

Parameter	Value
LED type	2835
LED quantity	96
Lifespan	35000
Power Factor	0,9
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor and outdoor use	YES
IEC protection class	II
IK protection rating	08
Full box quantity	10 pc
Lamp's warm-up time to 60%	1
Length	650 mm
Width	82 mm
Height	60 mm
Product weight with packaging	382 g
Energy class	A++
Power	• 30 W

Material (cover)	polycarbonate
Material (housing)	Polycarbonate

Voltage	• 185-265 V AC
Correlated colour temperature	• 4000 K

**Single packaging**




Width	650 mm
Height	60 mm
Length	82 mm
Weight	0,7 kg
	1

**Bulk packaging**



Number of pieces/tape in meters pack zb	10 szt.
Width	660 mm
Height of collective packaging	190 mm
Length	330 mm
Weight	7,35 kg
Volume	0,041 m <sup>3</sup>

**Europallet**



Number of pieces/tapes in meters euro pallet	270
Quantity collective euro pallet	300 szt.
Weight of a euro pallet	220,5 kg
Pallet height	1900 mm
Quantity in 1 layer	30 szt.
Number of layers	10