

LED line LITE

Code: 477620

EAN: 5907777477620

LED line LITE TRI-PROOF 70W 4000K
1550mm



Technical data

Parameter	Value
Luminous efficacy	120 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	8400 lm
Colour consistency in McAdam ellipses	≤6
Standby power	0
IP protection rating	IP65
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	35 000
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
CRI colour rendering index	80
Colour	White
The lumen maintenance factor	96 %
Beam angle	120 °
Material (cover)	polycarbonate
Material (housing)	Polycarbonate


Parameter	Value
LED type	2835
LED quantity	192
Lifespan	35000
Power Factor	0,9
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor and outdoor use	YES
IEC protection class	II
IK protection rating	08
Full box quantity	10 pc
Lamp's warm-up time to 60%	1
Length	1550 mm
Width	82 mm
Height	48 mm
Energy class	A++
Power	• 70 W
Voltage	• 185-265 V AC
Correlated colour temperature	• 4000 K

LED line LITE TRI-PROOF 70W 4000K
1550mm


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	1550 mm
Height	48 mm mm
Length	82 mm mm
Weight	1,1 kg kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	10 szt.
Width	1560 mm mm
Height of collective packaging	190 mm
Length	270 mm mm
Weight	11,35 kg
Volume	0,080 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	170
Quantity collective euro pallet	1600 szt.
Weight of a euro pallet	1816 kg kg
Pallet height	1900 mm
Quantity in 1 layer	160 szt.
Number of layers	10

LED line LITE

Code: 477620

EAN: 5907777477620

**LED line LITE TRI-PROOF 70W 4000K
1550mm**

Example application