

LED line PRIME

Code: 216792

EAN: 5905378216792

**Street luminaire CAMINO 4000K 70W
9800 lm IP66 gray PRIME**



CAMINO 70W road mounting from LED line PRIME is an advanced solution with light performance of 9800 lm. It is characterized by a colour temperature of 4000 K, which provides natural, white light. Made of aluminium and tempered glass, it achieves a high level of protection IP66 and IK08, guaranteeing resistance to atmospheric conditions and mechanical damage. It works in voltage range 220-240 V AC.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 70 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	9800 lm
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	75000 h

Parameter	Value
L90B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	50000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
ULOR	0 %
Frequency of the supply voltage	50/60Hz
Beam angle	150 x 110
LED type	LUMILEDS 2835
LED quantity	96
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷50
For indoor use	Outside
Height	80
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass

LED line PRIME


Code: 216792

EAN: 5905378216792

**Street luminaire CAMINO 4000K 70W
9800 lm IP66 gray PRIME**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Width	514 mm
Height	80 mm
Length	200 mm
Weight	2,3 kg

Bulk packaging

Quantity	1
Width	5600 mm
Height	1160 mm
Length	2360 mm
Volume	15,33 m3
Weight	

Europallet

Height	1840 mm
Number of layers	1
Bulk quantity	96
Weight	330,4 kg

LED line PRIME

Code: 216792

EAN: 5905378216792

**Street luminaire CAMINO 4000K 70W
9800 lm IP66 gray PRIME**

Example application

