

LED line PRIME

Code: 470225-II

EAN: 5905378201552

**LED bulb GU10 4000K 10W 1250lm 230V
120° DIM Ceramic PRIME**



LED bulb GU10 10W 4000K 1250lm from LED line PRIME is an innovative light source that delivers performance of 125 lm/W. It offers natural white colour of light, ideal for a variety of interiors. Thanks to a light angle of 120°, the light is distributed evenly. Additionally, the TRIAC dimming function allows for precise brightness adjustment. The product has a durability of up to 30,000 hours and resistance to more than 50,000 on/off cycles.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 10 W
Voltage	• 170-250 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	125
Luminous flux	1250 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	Triac

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Lamp's type	GU10
Beam angle	120 °
LED type	SMD2835
Compatible dimmer type	TRIAC
Power Factor	0,7
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
For indoor use	Inside
Height	55 mm
Colour	White
Material	Ceramic
Material (housing)	Ceramics


LED line PRIME

Code: 470225-II


EAN: 5905378201552

**LED bulb GU10 4000K 10W 1250lm 230V
120° DIM Ceramic PRIME**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	50 mm
Height	63 mm
Length	50 mm
Weight	0,065 kg

Bulk packaging

Quantity	100
Width	280 mm
Height	155 mm
Length	575 mm
Volume	0,024 m3
Weight	7 kg

Europallet

Quantity	4800
Height	1,90 m
Quantity in layer	
Number of layers	
Bulk quantity	48
Weight	445 kg

LED line PRIME

Code: 470225-II

EAN: 5905378201552

**LED bulb GU10 4000K 10W 1250lm 230V
120° DIM Ceramic PRIME**

Example application

