

LED line PRIME

Code: 470225-II

EAN: 5905378201552

LED BULB GU10 10W 4000K 1250lm
DIMMABLE PRIME



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	125 lm/W	Lamp's diameter	50
Colour of the light	White	Beam angle	120 °
Energy efficiency class 2019/2015	E	Material (housing)	Ceramic
Luminous flux	1250 lm	LED type	SMD2835
Colour consistency in McAdam ellipses	≤6	Compatible dimmer type	TRIAC
IP protection rating	IP20	Lifespan	30000
Warranty (years)	5	Power Factor	0,7
Dimmable function	Triac	Number of on/off cycles	50000
Survival factor	0.9	Colour consistency in McAdam ellipses	≤6
Lifetime L70B50	30 000	For indoor use	Inside
Material	Ceramic	Full box quantity	100 pc
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	80	Height	55 mm
Colour	White	Power	• 10 W
The lumen maintenance factor	96 %	Voltage	• 170-250 V AC
Lamp's type	GU10	Correlated colour temperature	• 4000 K

LED line PRIME

Code: 470225-II

EAN: 5905378201552


LED BULB GU10 10W 4000K 1250lm
DIMMABLE PRIME

Dimensions

Light distribution


Additional product photos

Logistics data




Single packaging

Width	50 mm
Height	63 mm mm
Length	50 mm mm
Weight	0,06 kg kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	575 mm mm
Height of collective packaging	155 mm
Length	280 mm mm
Weight	7 kg kg
Volume	0,024 m3 m3



Europallet

Quantity collective euro pallet	4800 szt.
Weight of a euro pallet	336 kg
Pallet height	1860 mm
Quantity in 1 layer	400 szt.
Number of layers	12

LED line PRIME

Code: 470225-II

EAN: 5905378201552

**LED BULB GU10 10W 4000K 1250lm
DIMMABLE PRIME**

Example application