

LED line LITE Code: 209947 EAN: 5905378209947

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1120lm round white





Downlight EASY FLEX 9-12-15W CCT 1120Im is a modern round LED line LITE lighting product. Its high light efficiency is 1120 lumens at power expenditure 9, 12 or 15 W, which provides excellent lighting conditions. Thanks to the possibility to choose the temperature of the colour of light (3000 K, 4000 K, 5000 K) and the universal assembly (mountain, surface and suspended), DOWNLIGHT fits perfectly into various interior arrangements.



















Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	75
Energy efficiency class 2019/2015	E
Luminous flux	1120
Colour consistency in McAdam ellipses	≤ 6
Warranty (years)	3
IP protection rating	IP20
Survival factor	0.9
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96
Fixture's diameter	170

Parameter	Value
Beam angle	120
LED type	SMD2835
LED quantity	84
Number of on/off cycles	15000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	`-20 ÷ 40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-130
IEC protection class	II
IK protection rating	05
Lamp's warm-up time to 60%	1s
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Power	• 9 W • 12 W • 15 W




LED line LITE Code: 209947 EAN: 5905378209947

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1120lm round white

Technical drawing

Light distribution

Luminous [cd/klm]



Additional product photos












Logistics data







Single packaging

Bulk packaging

Europallet

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 209947 EAN: 5905378209947

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1120lm round white

Example application