

LED line LITE

Code: 247439

EAN: 5901583247439

LED bulb E27 4000K 15W 1515lm 230V
240° A60 PC LITE



LED bulb E27 15W 4000K 1515lm from LED line LITE is an advanced lighting solution that provides light performance of 101 lm/W. Neutral colour temperature 4000 K guarantees optimal color reproduction and visual comfort. The combined luminous flux of 1515 lm and a lighting angle of 240° allow effective lighting of the rooms. The durability of the product reaches as much as 50,000 hours and the power factor is 0.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 15 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	101
Luminous flux	1515 lm
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	240 °
Lifespan	50 000 h
Power Factor	0,5
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	119
Fixture's diameter	60 mm
Material (housing)	Polycarbonate

LED line LITE


Code: 247439

EAN: 5901583247439

LED bulb E27 4000K 15W 1515lm 230V
240° A60 PC LITE




Technical drawing

Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	1
Width	61 mm
Height	110 mm
Length	61 mm
Weight	0,05 kg

Bulk packaging

Quantity	100
Width	320 mm
Height	270 mm
Length	625 mm
Volume	0,054 m3
Weight	4,5 kg
Comments	

Europallet

Quantity	1500
Height	1890 mm
Quantity in layer	300
Number of layers	7
Bulk quantity	2100
Weight	94,5 kg

LED line LITE

Code: 247439

EAN: 5901583247439

**LED bulb E27 4000K 15W 1515lm 230V
240° A60 PC LITE**

Example application