

LED line LITE Code: 207486 EAN: 5905378207486

Park Luminaire PARKLITE 50W CCT 6000lm black LITE





PARKLITE 50W CCT 6000lm in black is an innovative 50W light source. Equipped with SMD LEDs, 2835 delivers high light performance of 120 lm/W, generating a total luminous flux of 6000 lumens. It is characterized by energy efficiency class E and power factor PF 0.9. The housing has a degree of protection IP65 and IK08, which guarantees resistance to atmospheric conditions and mechanical damage.





















Technical data

Parameter	Value
ULOR	2,3 %
Voltage	• 220-240 V AC
Luminous efficacy	120
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	6000
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	25 000 h
Wire length	400 mm
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96

Parameter	Value
Beam angle	100
Material (cover)	tempered glass
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	384
Power Factor	0,9
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-30÷50
IEC protection class	I
IK protection rating	08
Lamp's warm-up time to 60%	ls
Correlated colour temperature	3000 K4000 K6000 K
Power	• 50 W




LED line LITE Code: 207486 EAN: 5905378207486

Park Luminaire PARKLITE 50W CCT 6000lm black LITE

Technical drawing

Light distribution

Luminous [cd/klm]



Additional product photos












Logistics data







Single packaging

Bulk packaging

Europallet

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 207486 EAN: 5905378207486

Park Luminaire PARKLITE 50W CCT 6000lm black LITE

Example application